Technical Data Sheet



FLED30W

LED Flood Light

Grey Finish

Dimensions

Depth Width Height 130mm 230mm 185mm



Specifications

Weight 2.2KG
Colour Grey
Housing material Cast Aluminium
IP Rating IP65

Approval

AS/NZS 60598.2.5:2002

SAA122626

Features

- Easy to install
- Power efficient
- Economic to run
- Long life
- Saves power and emissions
- Suitable for inside/outside use

Technical Data Sheet

Product Use

The FLED30W is used to efficiently light wide areas

Typical applications:

- Yard Lighting
- Security Lighting
- Sheds
- Warehouse lighting
- Display lighting

Environmental Conditions

Operation to IEC 721-3-3
Climatic conditions class 3K5
Temperature 0...+60°C
Humidity <95% r.h.

Standards

Test standards A/S NZS

60598.2.5:2002

Approval SAA122626

EMC Compliance This is a Class One

Device that has a low risk of electrical

interference

Performance

Light Output 2350Lm

Replaces 60W Halogen Lamp life 30000Hrs Colour Temp 4000K

Beam Angle 140/60Deg
CRI >70 RA

Not Dimmable

Ordering

When ordering please give name and type,

Reference FLED30W

Barcode 420004902055

Technical Data

Power Supply 230 VAC
Power Factor > 0.904
Supply Line Fusing max. 10A
For Solid Wires 2 x 1.5mm²